


DMG10600C101_40WTC



● System Hardware

Properties	Parameters
Motherboard level	Commercial-grade
CPU	RK3566, Quad-core ARM Cortex-A55, 1.8GHz Processor
OS	Linux 4.19
Storage	8Gbytes eMMC
RAM	2Gbytes LPDDR4

● Display Parameters

Properties	Parameters	Description
Size	10.1 inch	-
LCD Type	IPS, TFT LCD	-
Viewing Angle	85° /85° /85° /85°	Wide viewing angle, high contrast, and good color reproduction
Active Area (AA)	222.72mm (W)*125.28mm (H)	-
Resolution	1024x600	-
Backlight Service Life	>20000 Hrs	Backlight service life refers to the period the LED backlight operates under test conditions until brightness decreases to 50% of the initial level
Brightness	200nit	100-level brightness adjustment (Flickering may occur at 1%-30% of max brightness; not recommended for use in this range)

Note: Use dynamic screen saver to prevent afterimages from prolonged fixed page display.

● Touch Parameter

Properties	Parameters
Touch Type	Capacitive touch panel
Structure	G+G structure with tempered glass surface

● Power Supply

Properties	Min	Typ	Max	Unit
Power Voltage	9.0	12.0	23.0	V


Recommended power supply:12V 1A DC.

● Environment & Reliability Test

Properties	Conditions	Min	Typ	Max	Unit
Working Temperature	60%RH at 12V voltage	-10	25	60	℃
Storage Temperature	-	-20	25	70	℃
Working Humidity	25℃	10%	60%	90%	RH
Conformal Coating	Y				
ESD	Air: ±8KV; Contact: ±6KV				
EFT	Group pulse interference ±2KV				
CE Certification	Y				

● Peripherals and Interfaces

Properties	Description
User Interface	10Pin_3.81mm Horizontal socket
COM	RS232*2(COM5 & COM9), RS485*1(COM8), TTL*1(COM0)
Wi-Fi	IEE 802.11Bb/g/n, 2.4GHz, Bluetooth
Bluetooth	4.2GHz
Ethernet	10/100Mbps
USB	USB 2.0*2(HOST),Micro USB*1(OTG)
SD Card	Max 64G
RTC	Accuracy: $\pm 20\text{ppm}$ @25°C
Speaker	2Pin_1.25mm interface*1
Microphone	2Pin_1.25mm interface*1
Headphone	3.5mm spacing interface
Camera	USB, not supported by MIPI
4G module	Factory not configured, customizable to add
HDMI interface	HDMI*1





- **Development Platform**

Development	
QT	QTCreator2.7.2 and above

- **Packing Capacity & Dimension**

Dimension				
Dimension	257.81(W)*148.08(H)*23.20(T)mm			
Net Weight	620g			
Packing Capacity				
Model	Size	Layer	Quantity/Layer	Quantity(Pcs)
Carton1:	220mm(L)*160mm(W)*47mm (H)	-	-	-
Carton2:	250mm(L)*200mm(W)*80mm (H)	-	-	-
Carton3:	320mm(L)*270mm(W)*80mm (H)	2	1	2
Carton4:	450mm(L)*350mm(W)*300mm(H)	1	10	10
Carton5:	600mm(L)*450mm(W)*300mm(H)	1	16	16

DWIN Technology Technical Document



Definition	Pin#	I/O	Description
VCC	1	P	Power Input
GND	2	P	GND
485A	3	A	RS485+
485B	4	B	RS485-
RX0	5	I	Input
TX0	6	O	Output
RX5	7	I	Input
TX5	8	O	Output
RX9	9	I	Input
TX9	10	O	Output

Location hole is used as position reference.
 Unmarked Tolerance is +/-0.3mm
 Active area is marked in Dash lines

Model	DMG10600C101-40WTC			DWIN Technologies		
Drawing	A 4	Drawn	G. Y		Date	2023.01.06
Scale	1 : 1	Review			Date	
Unit	MM	Approval			Date	

Revision Records

Rev.	Revise Date	Content	Editor
00	2023-02-24	First edition	YML
01	2023-05-15	Remove the 4G module and update the physical image	YML
02	2025-01-03	Modify the voltage value range, add development	Chen
03	2025-03-12	Add the description of Bluetooth	Chen

Please contact us if you have any questions about the use of this document or our products, or if you would like to know the latest information about our products:

Customer service Tel: +86-400-018-9008

Customer service E-mail: dwinhmi@dwin.com.cn

Website: www.dwin-global.com

DWIN Developer Forum: <https://forums.dwin-global.com/index.php/forums>

Thank you all for continuous support of DWIN, and your approval is the driving force of our progress!

Important Disclaimer

DWIN reserves the right to make any changes to product designs without prior notice.

Customers should ensure strictly adhering to all the relevant standards and requirements during the product application process, including but not limited to functional safety, information security, and regulatory provisions.

DWIN shall not bear any joint and several liability for any consequences that may arise from customers' adoption of DWIN products. In particular, for risks that may lead to significant property losses, environmental hazards, personal injury, or even death, especially in high-risk application areas such as military applications, flammable and explosive places, and life-saving medical equipment, customers should independently assess the risks and take corresponding preventive and protective measures. DWIN shall not bear any relevant responsibility.