DMG10600T070_40WTC



DWIN Technology 1 www.dwin-global.com

System Hardware

Properties	Parameters		
Motherboard level	Industrial-grade		
CPU	RK3566, Quad-core ARM Cortex-A55, 1.8GHz Processor		
os	Linux 4.19		
Storage	8Gbytes eMMC		
RAM	2Gbytes LPDDR4		

Display Parameters

Properties	Parameters	Description		
Size	7.0 inch	-		
LCD Type	IPS, TFT LCD	-		
Viewing Angle	85° /85° /85° /85°	Wide viewing angle, high contrast, and good color reproduction		
Active Area (AA)	154.08mm(W)×85.92mm (H)	- ×		
Resolution	1024×600	-		
Backlight Service Life	>20000 Hrs	Backlight service life refers to the period the LED backlight operates under test conditions until brightness decreases to 50% of the initial level		
Brightness	250nit	100-level brightness adjustment (Flickering may occur at 1%-30% of max brightness; not recommended for use in this range)		
Note: Use dynamic screen saver to prevent afterimages from prolonged fixed page display.				

Touch Parameter

Properties	Parameters		
Touch Type	Capacitive touch panel		
Structure	G+G structure with tempered glass surface		

Power Supply

Properties	ties Min Typ		Max	Unit	
Power Voltage	9.0	12.0	36.0	V	
Recommended power supply:12V 1A DC.					


Environment & Reliability Test

Properties	Conditions	Min	Тур	Max	Unit
Working Temperature	60%RH at 12V voltage	-10	25	65	$^{\circ}$
Storage Temperature	-	-30	25	80	$^{\circ}$
Working Humidity	25℃	10%	60%	90%	RH
Conformal Coating	Y				
ESD	Air: ±8KV, Contact: ±6KV				
RE	Class B				
CE Certification	Y				
Additional cooling required for operation above 65°C.					

DWIN Technology 2 www.dwin-global.com

Peripherals and Interfaces

Properties	Description		
User Interface	10Pin_3.81mm horizontal socket, power interface (3PIN_Φ2.0DH)		
СОМ	RS232*2 (COM5 & COM9), RS485*1(COM7), RS232/TTL*1 (COM0, RS232 default), TTL*1(COM2, debug)		
USB	USB 2.0*2 (HOST), Type C*1 (OTG)		
Headphone	3.5mm spacing interface *1		
Speaker	2Pin_1.25mm interface *1		
Microphone	2Pin_1.25mm interface *1		
4G module	Factory not configured, customizable to add		
Camera	MIPI (24Pin_0.5mm interface)		
SD card	Max. 64G		
LAN	10/100Mbps		
Wi-Fi	IEEE 802.11Bb/g/n, 2.4GHz, Wi-Fi 4		
Bluetooth	BT4.2		
RTC	Accuracy: ±20ppm @25°C		
GPIO Interface	GPIO*6		




DWIN Technology 3 www.dwin-global.com

Development Platform

Development	
Qt	QtCreator2.7.2 and above

Packing Capacity & Dimension

Dimension	190.50(W)×105.41(H)×24.37(T)mm			
Net Weight	340g			
Packing Capacity				
Model	Size	Layer	Quantity/Layer	Quantity (Pcs)
Carton1:	220mm(L)×160mm(W)×47mm	-	-	-
Carton2:	250mm(L)×200mm(W)×80mm	2	1	2
Carton3:	320mm(L)×270mm(W)×80mm	2	2	4
Carton4:	450mm(L)×350mm(W)×300mm	1	10	10
Carton5:	600mm(L)×450mm(W)×300mm	1	SCHIME II	20
	600mm(L)×450mm(W)×300mm			



Revision Records

Rev.	Revise Date	Content	Editor
00	2025-02-17	First Edition	Chen
01	2025-03-12	Add the description of Bluetooth	Chen
02	2025-06-16	Update the appearance and rang of temperature & Update the description of Wi-Fi module	Chen

Please contact us if you have any questions about the use of this document or our products, or if you would like to know the latest information about our products:

Customer service Tel: +86-400-018-9008

Customer service E-mail: dwinhmi@dwin.com.cn

Website: www.dwin-global.com

DWIN Developer Forum: https://forums.dwin-global.com/index.php/forums

Thank you all for continuous support of DWIN, and your approval is the driving force of our progress!

Important Disclaimer

DWIN reserves the right to make any changes to product designs without prior notice.

Customers should ensure strictly adhering to all the relevant standards and requirements during the product application process, including but not limited to functional safety, information security, and regulatory provisions.

DWIN shall not bear any joint and several liability for any consequences that may arise from customers' adoption of DWIN products. In particular, for risks that may lead to significant property losses, environmental hazards, personal injury, or even death, especially in high-risk application areas such as military applications, flammable and explosive places, and life-saving medical equipment, customers should independently assess the not b

Rechnology

Rechnology risks and take corresponding preventive and protective measures. DWIN shall not bear any relevant responsibility.