


DMG19108C156_43WTCZOS-1





DWIN Technology 1 www.dwin-global.com



System Hardware

Properties	Parameters	
Motherboard Level Commercial-grade		
СРИ	RK3566, Quad-core ARM Cortex-A55 1.8GHz Processor	
OS Linux 4.19		
RAM	2Gbytes LPDDR4	
Storage	8Gbytes eMMC	

Display Parameters

Properties	Parameters	Description	
Size	15.6 inch	-	
Viewing Area (VA)	343.76mm (W)×193.19mm (H)	- X	
Resolution	1920×1080		
Backlight Service Life	>20000 Hrs	Backlight service life refers to the period the LED backlight operates under test conditions until brightness decreases to 50% of the initial level	
Brightness	100nit	100-level brightness adjustment (Flickering may occur at 1%-30% of max brightness; not recommended for use in this range)	
Note: Use dynamic screen saver to prevent afterimages from prolonged fixed page display.			

Touch Parameter

Properties	Parameters
Touch Type	Integrated black capacitive touch panel, the bonding of the LCD panel to the touch panel with OCA process, 10mm uniform black touch bezel (all sides)

Power Supply

Properties	Min	Тур	Max	Unit	
Power Voltage	12.0	12.0	36.0	V	
Recommended power supply:12V 1A DC.					

Environment & Reliability Test


Properties	Conditions	Min	Тур	Max	Unit
Working Temperature	60%RH at 12V voltage	0	25	50	°C
Storage Temperature	-	-10	25	60	$^{\circ}\mathbb{C}$
Working Humidity	25℃	10%	60%	90%	RH
Conformal Coating	Y				
Enclosure	Anodized aluminum enclosure				
ESD	Air: ±8KV				
RE	Class A				
Additional cooling required for operation above 50°C.					

DWIN Technology 2 www.dwin-global.com

Peripheral and Interfaces

Properties	Description
User Interface	DB9 female Right-Angle receptacle, power interface (3PIN_Φ2.0DH)
СОМ	RS232*2 (COM5 & COM9), RS485*1(COM8), TTL*1 (COM0)
Ethernet	10/100Mbps
USB	USB *2 (HOST), Type C*1 (OTG)
SD Card	Max 64G
Wi-Fi	IEEE 802.11a/b/g/n/ac/ax, 2.4GHz + 5GHz, Wi-Fi 6 and backward compatibility
Bluetooth Version	BT5.2
RTC	Accuracy: ±20ppm @25℃
Speaker	2Pin_1.25mm interface*1
Keys	Recovery, Power, Mute





DWIN Technology 3 www.dwin-global.com



Development Platform

Development		
Linux	Debian 10	

Packing Capacity & Dimension

Dimension					
Dimension	367.06(W)×216.49(H)×39.00(T)m	367.06(W)×216.49(H)×39.00(T)mm			
Net Weight	-	-			
Packing Capacity					
Model	Size Layer Quantity/Layer Quantity (Pcs				
Carton1:	220mm(L)×160mm(W)×47mm	220mm(L)×160mm(W)×47mm -		-	
Carton2:	250mm(L)×200mm(W)×80mm				
Carton3:	320mm(L)×270mm(W)×80mm	320mm(L)×270mm(W)×80mm			
Carton4:	450mm(L)×350mm(W)×300mm	450mm(L)×350mm(W)×300mm			
Carton5:	600mm(L)×450mm(W)×300mm 1 5 5				

Standard Accessories

Accessories Name	Description
External Wi-Fi Antenna	Black, antenna (Qty:2)




Antenna configuration diagram

Optional Accessories

Accessories Name	Description
	Clips No.1 (Qty:4)
	Clips No.2, 19.9×11×4mm, 1.0mm galvanized steel sheet (Qty:4)
C156-31WTCZJ	M3×20mm white screws with integrated washer (Qty:4)
	M3×5mm, black 304 stainless steel pan head screws (Qty:6)
	Dimensions: 170×13×13mm, 1.0mm galvanized steel sheet, 15.6 inch black anodized aluminum left/right bracket set (Qty:1)



Bracket & clip mounting assembly diagram





Revision Records

Rev.	Revise Date	Content	Editor
00	2025-08-29	Initial release	Chen Xian

Please contact us if you have any questions about the use of this document or our products, or if you would like to know the latest information about our products:

Customer service Tel: +86-400-018-9008

Customer service E-mail: dwinhmi@dwin.com.cn

Website: www.dwin-global.com

DWIN Developer Forum: https://forums.dwin-global.com/index.php/forums

e driving forc.

Rechtlift

Recht Thank you all for continuous support of DWIN, and your approval is the driving force of our progress!



Important Disclaimer

DWIN reserves the right to make any changes to product designs without prior notice.

Customers should ensure strictly adhering to all the relevant standards and requirements during the product application process, including but not limited to functional safety, information security, and regulatory provisions.

DWIN shall not bear any joint and several liability for any consequences that may arise from customers' adoption of DWIN products. In particular, for risks that may lead to significant property losses, environmental hazards, personal injury, or even death, especially in high-risk application areas such as military applications, flammable and explosive places, and life-saving medical equipment, customers should independently assess the all not t

all not t

pertund to by

Pertund to by risks and take corresponding preventive and protective measures. DWIN shall not bear any relevant responsibility.