



DMG24240F013_05WN

Features:

- Powered by T5F0 ASIC, running DGUS II HMI platform.
- 1.30-inch, 240*240 resolution, IPS-TFT LCD, Circular LCD screen.
- 20 pins, including UART2, SD card, Buzzer, touch screen interface.
- Supporting connected to 4-wire RTP, CTP, buzzer or speaker.



1. External interface



PIN#	Definition1	Function1	Definition2	Function2
1	VIN	Power supply, DC4.5-5.5V. IO are all at 3.3V CMOS level.		
2	VIN			
3	GND			
4	GND	GND		
5	GND			
6	3.3V			
7	TX2	UART2		
8	RX2			
9	SD_D0	When JIOS is in the air, SD card interface.	TMS	When JIOS is shorting circuit to ground, JTAG interface.
10	SD_D1		TCK	
11	SD_D2		TDI	
12	SD_D3		TDO	
13	SD_CLK		TX1	Multiplexed UART1
14	SD_CMD		RX1	
15	CTP_SDA	Capacitive touch screen interface. When connected to CTP, the CTP_SDA and CTP_INT need to be pulled up to 3.3V by an external 4.7K resistance.		
16	CTP_INT			
17	CTP_SCL			
18	CTP_RST			
19	JIOS	JTAG/IO choose		
20	BUZZ	Buzzer drives output	D/A	Audio PWM DA output

2. Specification parameters

2.1 Product parameters

Main Chip	T5F0
User Interface	20Pin_0.5mm FCC
FLASH	8M Bytes
UI Version	DGUS II
Debugging Tools	HDL662SZ5 adapter board power supply
Size	1.30 inch
Resolution	240*240
Active Area (AA)	Diameter=32.40mm
Viewing Angle	Wide viewing angle (85°/85°/85°/85° typical), high contrast, and good color reproduction.
Backlight Service Life	>20,000 hours
Brightness	250nit
Brightness Control	100-level brightness adjustment (Flickering may occur at 1%-30% of max brightness; not recommended for use in this range)
Note: Use dynamic screen saver to prevent afterimages from prolonged fixed page display.	

2.2 Interface parameters

Item	Conditions	Min	Typ	Max	Unit
Baud Rate	User Set(Configure the CFG file)	3150	115200	3225600	bps
Output Voltage(TXD)	Output 1	3.0	3.3	-	V
	Output 0	-	0	0.3	V
Input Voltage(RXD)	Input 1	-	-	3.3	V
	Input 0	0	-	0.5	V
Interface	UART2: TTL;				
Data Format	UART2: N81;				

2.3 Electrical specifications

Rated Power	<2W	
Operating Voltage	4.5-5.5V, typical value of 5V.	
Operating Current	102mA	VCC=5V, max backlight.
	40mA	VCC=5V, backlight off.
Recommended power supply: 5V 1A DC.		

2.4 Operating environment

Operating Temperature	-10℃ to 60℃(5V @ 60% RH)
Storage Temperature	-20℃ to 70℃
Operating Humidity	10%-90%RH, typical value of 60% RH.

3. ESD Test

Test temperature: 25° C. Test humidity: 50%RH.

Test process: Place the product on the test bench fixture (approximately 15cm in height), and perform contact and air discharge tests on the smart LCM. Observe if any freezing, black or white screen, flickering, or rebooting occurs during the test.

Test conclusion: The product's ESD performance meets GB/T 17626.2 Class B standards.


Discharge Type	Discharge Value	Result
Air discharge	±8KV	Normal operation

4. Debug

It is recommended for new users of DWIN smart LCMs to purchase official accessories. For more details, please refer to customer service center.

Adapter board model: HDL662SZ5


Connecting cables: FCC20_0.5, L=50mm(B03692)




5. Packing capacity & dimension

Dimension				
Dimension	35.60(W) ×37.74(H) ×1.53(T) mm			
Net Weight	5g			
Packing Capacity				
Model	Dimensions	Layer	Quantity/Layer	Quantity(Pcs)
Carton1:	220mm(L)×160mm(W)×47mm(H)	1	4	4
Carton2:	250mm(L)×200mm(W)×80mm(H)	1	8	8
Carton3:	320mm(L)×270mm(W)×80mm(H)	1	16	16
Carton4:	455mm(L)×290mm(W)×240mm(H)	-	-	-


Front view



Side view



Back view



Socket definition

PIN#	Name
1	+5V
2	+5V
3	GND
4	GND
5	GND
6	3.3V
7	TX2
8	RX2
9	SD_D0
10	SD_D1
11	SD_D2
12	SD_D3
13	SD_CLK
14	SD_CMD
15	TPY1
16	TPY1
17	TPY0
18	TPX0
19	J10S
20	BUZZ

REVISION RECORD		VER	DATE	DWIN Technology			
1	First Edition	VI-1	20250902	FILE NAME : DMG24240F013.05MM		TOLERANCES : $\pm 0.1^{\circ}$	
2				CUSTOMER NAME :		SENSOR: ANGLES : $\pm 0.1^{\circ}$	
3				DESIGN :		RELEASE: VI-1 SCALE : 1:1	
4				DRAWN BY	DATE	20250902	UNIT : mm
5				CHECKED BY	DATE		PRO. (3)
6				APPROVED BY	DATE		SHEET : 1/1

6. Revision records

Rev	Revise Date	Content	Editor
00	2025-09-11	First Edition	Xu Ying

Please contact us if you have any questions about the use of this document or our products, or if you would like to know the latest information about our products:

- Customer service Tel: +86 400 018 9008
- Customer service email: dwinhmi@dwin.com.cn
- DWIN Developer Forum: <https://forums.dwin-global.com/>

Thank you all for continuous support of DWIN, and your approval is the driving force of our progress!

Important Disclaimer

DWIN reserves the right to make any changes to product designs without prior notice.

Customers should ensure strictly adhering to all the relevant standards and requirements during the product application process, including but not limited to functional safety, information security, and regulatory provisions.

DWIN shall not bear any joint and several liability for any consequences that may arise from customers' adoption of DWIN products. In particular, for risks that may lead to significant property losses, environmental hazards, personal injury, or even death, especially in high-risk application areas such as military applications, flammable and explosive places, and life-saving medical equipment, customers should independently assess the risks and take corresponding preventive and protective measures. DWIN shall not bear any relevant responsibility.